Unit Comparison (see individual data sheets for more information, or call 01622 741122)

Unit Designation	**P4225**	**P4200**	**P4205**	**P4205'X'**	**P4206**	**P4215**
Voltage	24V	30V	30V	30V	30V	48V
Rated Capacity	10 Ah	5 Ah	10 Ah	10 Ah	10 Ah	10 Ah
Max Standing load (ask for details)	1 amp	None	1 amp	1 amp	1 amp	1 amp
Alarm Types						
Charger fail	Yes	None	Yes	Yes	Yes	Yes
Battery volts low	Yes	None	Yes	Yes	Yes	Yes
Battery volt high	Yes	None	Yes	Yes	Yes	Yes
No. of outputs	2	1	2	2	3	2
Recharge time	6 hours	10 hours	6 hours	6 hours	6 hours	6 hours
Int/External use	Interior	Interior	Interior	Exterior	Interior	Interior
Mounting	Wall	Wall	Wall	Wall or post	Wall	Wall
Locks (Other options available)	Double-bit key cam lock	Double-bit key cam lock	Double-bit key cam lock	Concealed security lock	Double-bit key cam lock	Double-bit key cam lock
External dims						
W (mm)	500	300	500	530	500	500
H (mm)	500	380	500	700	500	500
D (mm)	300	210	300	265	300	300
Wt Approx:						
Unit (Not including battery pack)	28 kg	10.2kg	28kg	29kg	28kg	28kg
Complete battery pack	9kg	5.6kg	11.2kg	11.2kg	11.2kg	18kg
Protection category	IP31	IP31	IP31	IP55	IP31	IP31
Climate control	-	-	-	Optional	-	-
Box construction	All round solid steel	All round solid steel	All round solid steel	Twin walled aluminium	All round solid steel	All round solid steel
Priming	-	-	-	Electrophoretic dipcoat	-	-
Paint Finish	Powder-coated	Powder-coated	Powder-coated	Powder-coated	Powder-coated	Powder-coated
Colour (Any colour available)	RAL 7035	RAL 7035	RAL 7035	RAL 7035	RAL 7035	RAL 7035